

Description

POLYSTYRENE IMPACT 8260 is an high impact polystyrene for extrusion and injection applications. This grade has an improved environmental stress crack resistance in comparison with standard high impact grades. The product has been specifically designed for the production of refrigerator part: inner liners, door liners, injected parts etc.

This grade is also proposed for the production of packaging intended for products likely to cause stress cracking e.g. fats, oil...

POLYSTYRENE IMPACT 8260 retains good mechanical properties at low temperatures making this grade suitable for frozen packaging; it also affords good printing performance.

Applications

Sheet for thermoforming, fridges liners, low temperature packaging applications (ice cream boxes and lids), packaging for aggressive foodstuffs, matt finish, soft touch.

Properties

Rheological	Method	Unit	Value
Melt flow index (200°C-5kg)	ISO 1133 H	g/10mn	2.8
Thermal			
Vicat softening point 10N (T° increase = 50°C/h)	ISO 306A50	°C	99
Vicat softening point 50N (T° increase = 50°C/h)	ISO 306B50	°C	90
Coefficient of linear thermal expansion		mm/°C	9.10 E-5
Mechanical			
Notched Charpy impact strength	ISO 179/1eA	KJ/m ²	11
Notched Izod impact strength	ISO 180/1A	kJ/m ²	11
Tensile strength at yield	ISO 527-2	MPa	20
Tensile strength at break	ISO 527-2	MPa	25
Elongation at break	ISO 527-2	%	>60
Tensile modulus	ISO 527-2	MPa	1600
Flexural modulus	ISO 178	MPa	1600
Electrical			
Dielectric strength		kV/mm	150
Surface resistivity	ISO IEC 93	Ohms	>10 E+13
Miscellaneous			
Density	ISO 1183	g/cm ³	1.04
Moulding shrinkage		%	0.4-0.7
Water absorption	ISO 62	%	<0.1

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use. Unless specifically indicated, the products mentioned herein are not suitable for applications in the pharmaceutical or medical sector. The Companies within Total Refining & Chemicals do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.



General Information

- Standard properties: All tests carried out at 23°C unless otherwise stated. Mechanical properties are measured on injection moulded tests specimens.
- Bulk density: bulk density is approximately 0.6 g/cm³.
- Please refer to the Safety Data Sheet for further information.
- Please refer to the safety data sheet (SDS) for handling and storage information. It is advisable to convert the product within six months after delivery provided storage conditions are used as given in the SDS of our product. SDS may be obtained from the website: www.totalrefiningchemicals.com

DISCLAIMER

Information contained in this publication is true and accurate at the time of publication and to the best of our knowledge. The nominal values stated herein are obtained using laboratory test specimens. Before using one of the products mentioned herein, customers and other users should take all care in determining the suitability of such product for the intended use, and particularly the conformity with current regulations. TOTAL PETROCHEMICALS do not recommend its polystyrene resins for use in any application in direct or indirect contact with human body fluids and tissues. The Companies within TOTAL PETROCHEMICALS do not accept any liability whatsoever arising from the use of this information or the use, application or processing of any product described herein. No information contained in this publication can be considered as a suggestion to infringe patents. The Companies disclaim any liability that may be claimed for infringement or alleged infringement of patents.